(108) y BASIS OF BEARING THE LINE BETWEEN FOUND MONUMENTS 102 AND 200 BEARS SOUTH 2'41' EAST, THE RECORD VALUE FROM MAP A-7283. NARRATIVE THE PURPOSE OF THIS SURVEY IS TO MONUMENT THE BOUNDARY OF THE TRACT OF LAND DESCRIBED IN INSTRUMENT #2005-005710 T.C.D.R.

HELD THE LINE BETWEEN MONUMENTS (102) AND (108) AS THE WEST LINE OF THE NORTH

1/2 OF SECTION 23 (MAP B-1707) HELD MONUMENTS (100), (101), (104), (105), AND

(107) AS DEED MONUMENTS, THEIR RELATIONSHIP MATCHES THE DEED TOO CLOSELY TO DISREGARD THEM. HELD CALCULATED DISTANCE FROM MAP B-1707 FROM 108 TO CONTROL THE MOST NORTHERLY CORNER OF THE SUBJECT PROPERTY SS MONUMENT NOTES 100) FOUND 3/4" IRON PIPE, RUSTY, IN FENCE LINE, LEANS WEST, TIED TOP OF PIPE. SEE MAP A-2395. HELD. ₩M 101) FOUND 3/4" THREADED IRON PIPE, RUSTY, IN FENCE LINE. SEE MAP A-2395. HELD. 102) FOUND 3" BRASS CAP IN CONCRETE, STAMPED "TILLAMOOK COUNTY SURVEYOR 1/4, S22 | S23, RS 793, 1969" SEE REWITNESS BOOK 134. HELD. 104) FOUND 1/2" IRON ROD. NOT OF RECORD. HELD. 105) FOUND 1/2" IRON ROD. NOT OF RECORD. HELD. (107) FOUND 1/2" IRON ROD. NOT OF RECORD. HELD. (108) FOUND 5/8" REBAR WITH YELLOW PLASTIC CAP STAMPED "HLB INC", SEE MAP B-1707. HELD FOR LINE. FOUND 5/8" REBAR, 0.2' ABOVE GROUND, SEE MAP A-2232, A-7283. HELD FOR BASIS OF BEARING. 201) FOUND 5/8" REBAR WITH YELLOW PLASTIC CAP STAMPED "D BARRETT LS 1979", SEE MAP B-1442. **LEGEND** O INDICATES SET 5/8" x 30" REBAR WITH YELLOW PLASTIC CAP STMAPED "J WICKMAN LS 73558". INDICATES FOUND MONUMENT AS NOTED HEREON. HELD FOR CONTROL. CORNER FALLS IN A INDICATES FOUND MONUMENT AS NOTED HEREON. HELD FOR BOUNDARY CONTROL. BEAVER DAM IN SCOVELL DEED BOOK 404, PAGE 762 BOB'S CREEK INDICATES FOUND MONUMENT AS NOTED HEREON. MONUMENT NOT SET INDICATES RECORD VALUE FROM DEED INSTRUMENT #2005-005780. INDICATES RECORD VALUE FROM MAP A-7283. ()2 INDICATES RECORD VALUE FROM MAP B-1707. ()3 INDICATES RECORD VALUE FROM MAP A-2395. NO () INDICATES MEASURED VALUE. (102) SCALE: GREEN DIAMOND RESOURCE DEED BOOK 317, PAGE 27 BROWER DEED BOOK 272, PAGE 606 1" = 100'SS (EAST 190.79') REGISTERED N 89'59'51" E 190.79' **PROFESSIONAL** (EAST 90') LAND SURVEYOR Ш Ш Ţ N 89'59'51 691.04°, 691.13′)¹ 89.66 BROWER DEED BOOK 272, PAGE 606 **OREGON** JULY 12, 2005 JOHN PETER WICKMAN 73558 RENEWS JUNE 30, 2008 CRS\BRI_KIM.DWG BUBLITZMEAS.SEE CASTLE ROCK SURVEYING BOUNDARY SURVEY FOR: BRIEN S. BUBLITZ LANDS DESCRIBED IN
DEED INSTRUMENT #2005-005710 T.C.D.R.
SW1/4 NW1/4 SECTION 23, T3N, R10W, W.M.
NW1/4 SW1/4 SECTION 23, T3N, R10W, W.M. P.O. BOX 1252 DATE CANNON BEACH, OR 97110 (503) 436-1218 TILLAMOOK COUNTY Frons of DATE 201) BEARS S 74.48'15" W 6.15' FROM 200) DRAWN CHECKED 200 JOB NO.

LEICA TC803 ONBOARD

JPW.AMH

JPW

APR. 4, 2006